

## Light efficiency:

n/a Lumen/Watt

## Light quality:

CRI: 91.7

## Color temperature:

3004 K

Output: 343 lm/ft

Peak: 106 cd

Power: 0.00 W

PF: n/a

No photo

## Product name:

ThermaLine 3 -3000K


## Item number:

AL-01-65-2462

## Date and time:

7/15/2025 9:48:34 AM

## Description:




Beam angle

109.2°






CIE 1931  
x: 0.436  
y: 0.402

## Spectra




## Power






**TM-30: 89.3**



**CRI: 91.7 (R1-R8)**



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
93.7	99.2	95.1	91.9	93.8	95.5	87.6	76.3	50.0	98.0	94.9	80.8	95.8	98.1	87.2


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
87.2	91.1	93.0	91.4	93.9	94.8	88.4	93.7	88.5	86.2	88.6	89.0	87.6	84.4	84.7	82.9

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
84.5	93.6	92.0	89.0	89.7	91.5	93.5	93.2	95.4	97.1	95.4	93.1	91.5	84.4	84.6

**CQS: 90.2**



### Color parameters

Color temperature	Color rendering Index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	$\Delta uv$
3004 K	91.7	50.0	89.3	96.2	90.2	0.436	0.402	0.251	0.347	-0.0008






**Rf 89.3**


Fidelity index Rf

**Rg 96.2**

Gamut index Rg

Hue Bin	R <sub>f</sub>	Shifts (%)	
		Chroma	Hue
1	87	-6%	2%
2	91	-3%	3%
3	93	-2%	3%
4	91	-5%	-2%
5	94	-5%	0%
6	95	-2%	0%
7	88	-7%	3%
8	94	-2%	4%
9	89	-1%	7%
10	86	2%	9%
11	89	5%	7%
12	89	6%	-3%
13	88	1%	-10%
14	84	1%	-13%
15	85	-4%	-7%
16	83	-5%	-11%





### Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
106lx	26lx	12lx	7lx	4lx	3lx	2lx	2lx	1lx	1lx	1lx	1lx	1lx	1lx	0lx	0lx	0lx	0lx	0lx	0lx
9.8fcd	2.5fcd	1.1fcd	0.6fcd	0.4fcd	0.3fcd	0.2fcd	0.2fcd	0.1fcd	0.1fcd	0.1fcd	0.1fcd	0.1fcd	0.1fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd

### Intensities in 0° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
106	105	102	96	88	76	62	50	40	34	29	22	6	1	1	1	1	1	1	1
100%	99%	96%	91%	83%	72%	59%	47%	38%	32%	27%	21%	6%	1%	1%	0%	1%	1%	1%	1%

### Intensities in 90° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
106	104	100	92	79	62	43	29	18	9	1	1	1	1	0	0	1	1	1	1
100%	99%	94%	87%	75%	59%	40%	27%	17%	9%	1%	1%	1%	0%	0%	0%	0%	1%	1%	1%

### Intensities in 180° c-plane


0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
106	105	102	96	88	76	62	50	40	34	29	22	6	1	1	1	1	1	1	1
100%	99%	96%	91%	83%	72%	59%	47%	38%	32%	27%	21%	6%	1%	1%	0%	1%	1%	1%	1%

### Intensities in 270° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
106	104	100	92	79	62	43	29	18	9	1	1	1	1	0	0	1	1	1	1
100%	99%	94%	87%	75%	59%	40%	27%	17%	9%	1%	1%	1%	0%	0%	0%	0%	1%	1%	1%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
109.2°	190.3°	204°	68.8%	47.7%

**iso-candela diagram**




10%	11 cd
20%	21 cd
30%	32 cd
40%	42 cd
50%	53 cd
60%	64 cd
70%	74 cd
80%	85 cd
90%	95 cd

Conditions:

Number of c-planes: 12

Candela at center: 106 cd

**iso-lux diagram**



Mounting height: 10 meters (33 feet)

3%	31.8m lx
5%	52.9m lx
10%	0.106 lx
30%	0.318 lx
50%	0.529 lx

Conditions:

Number of c-planes: 12

Lux at center: 1.06 lx

*Lux distribution on a surface  
when lamp is mounted at 10  
meters from the surface.*

p Ceiling	70	70	50	50	30	70	70	50	50	30
p Walls	50	30	50	30	30	50	30	50	30	30
p Floor	20	20	20	20	20	20	20	20	20	20
Room size X      Y	Viewing direction at right angles to lamp axis					Viewing direction parallel to lamp axis				
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a	n/a
Variation of the observer position for the luminaire distance S										
n/a	n/a					n/a				
n/a	n/a					n/a				
n/a	n/a					n/a				
CIE 117-1995. Corrected glare indices referring to 343 lm total luminous flux										


Viso Systems Aps – Copenhagen, Denmark – [www.visosystems.com](http://www.visosystems.com)

### Coefficients of Utilization

Ceiling reflectance	80				70				50			30			10			0
Wall reflectance	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
Floor reflectance	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	20	0
RCR	(RCR: Room Cavity Ratio) Room Values are expressed as percentage of Lumens delivered to the task surface																	
0	118	118	118	118	114	114	114	114	108	108	108	102	102	102	96	96	96	94
1	105	100	95	91	102	97	93	88	92	88	84	86	83	81	82	79	77	75
2	96	87	79	73	92	84	77	72	79	74	69	75	70	66	71	67	64	61
3	87	76	67	60	84	74	66	59	70	63	58	66	60	56	63	58	54	51
4	80	67	58	51	77	65	57	50	62	55	49	59	53	48	56	51	46	44
5	73	60	51	44	71	58	50	43	56	48	42	53	46	41	50	45	40	38
6	68	54	45	38	65	53	44	38	50	43	37	48	41	36	46	40	35	33
7	63	49	40	34	61	48	39	33	46	38	33	44	37	32	42	36	31	29
8	58	45	36	30	56	44	36	30	42	35	29	40	34	29	38	33	28	26
9	55	41	33	27	53	40	32	27	39	31	26	37	31	26	36	30	25	24
10	51	38	30	25	50	37	29	24	36	29	24	34	28	24	33	27	23	21

LAMPS (number of lamps)

Luminaire budgetary diagram




### Zonal Lumen Summary

0°-10°	10°-20°	20°-30°	30°-40°	40°-50°	50°-60°	60°-70°	70°-80°	80°-90°
{LUM0-10}	28.9 lm	44.2 lm	53.3 lm	53.6 lm	46.0 lm	36.4 lm	28.0 lm	20.7 lm
90°-100°	100°-110°	110°-120°	120°-130°	130°-140°	140°-150°	150°-160°	160°-170°	170°-180°
14.4 lm	5.32 lm	0.690 lm	0.456 lm	0.387 lm	0.335 lm	0.263 lm	0.171 lm	0.059 lm

**LCS table**


BUG rating:	B0 U2 G0	
Forward light	Lumens	Lumens %
Low(0-30):	41.6	12.1%
Medium(30-60):	76.5	22.3%
High(60-80):	32.2	9.4%
Very high(80-90):	10.3	3%
Back light		
Low(0-30):	41.6	12.1%
Medium(30-60):	76.5	22.3%
High(60-80):	32.2	9.4%
Very high(80-90):	10.3	3%
Uplight		
Low(90-100):	14.4	4.2%
High(100-180):	7.7	2.2%

**LCS graph**





### Warmup curve



### Warmup result

Warmup time:	Lamp stabilized in 15 min 1 sec
Warmup variation	+0.2%

### Warmup conditions

Stable period:	15 min
Stable change max:	2.0%
Minimum time:	15 min

### Color temperature change

CCT start	CCT change	CCT end
3004 K	0 K	3004 K


### Output change

Output start	Output change	Output end
343 lm	+1 lm	343 lm


**Flicker curve (complete sampled flicker signal)**



**Flicker frame (frame of one flicker period)**



**Flicker FFT (frequency scope of flicker curve)**



**Flicker results:**

Flicker frequency:		n/a Hz	
Flicker index:	n/a	JA8/10 40Hz	n/a %
Flicker percentage:	n/a %	JA8/10 90Hz	n/a %
SVM: (Visual flicker)	n/a	JA8/10 200Hz	n/a %
PstLM	n/a	JA8/10 400Hz	n/a %
Mp	n/a	JA8/10 1000Hz	n/a %

**Flicker conditions:**

Sample rate:	n/a samples/second
--------------	--------------------