

## AdaptDrive - 12V DC - 120W

AL-97-02-12120



The AdaptDrive is an all-in-one LED driver and dimmer that simplifies installation by fitting directly into a standard recessed electrical box—eliminating the need for a separate driver location. UL Listed AdaptDrive is available in a wide range of output options in both 12VDC and 24VDC configurations to suit a variety of low-voltage lighting applications.

This is the first driver of its kind to provide this level of power in such a compact footprint—making it ideal for high-output applications where space is limited.


- Constant Voltage Output in 12VDC
- Installs directly into standard wall boxes
- Clean white finish on trim
- First in its class for power density in a recessed enclosure

## QUICK SPECIFICATIONS

Input	<b>120V</b>	120V AC
Features	<b>100% Max. Load</b>	100% maximum load
Environment		Dry/damp environment
Certifications		UL/cUL/Class P/Type HL/SELFC/CE/ROHS/REACH
Warranty		6 year limited

# ALLOY LED® Specifications


## DIMENSIONS




## TECHNICAL INFORMATION


Item Number		AL-97-02-12120
Output	DC Voltage	12V DC
	Rated Current	10A
	Rated Power	120W
Input	Voltage Range	120V AC
	Input Current	1.1 A
	Frequency Range	60 Hz
	Power Factor (Avg.)	>99%
Protection	Short Circuit	Hiccup mode, recovers automatically after fault condition is removed
	Over Voltage	≥110% Constant current mode, recovers automatically after fault condition is removed
Environment	Working Temp.	-40~+60 °C / -104 ~ +140°F
	Humidity	20 - 95%RH non-condensing
Safety & EMC	Safety Standards	UL8750 CAN/CSA-C22.2 No.250.13 (US)
	EMC Emission	FCC Part15 Subpart B ANSI C63.4:2014 (US)
Other	Warranty	6 Year Limited
	Size	4.13 x 2.12 x 1.59 in.

DIMMING WIRING DIAGRAM



3-WAY DIMMING WIRING DIAGRAM





## TROUBLESHOOTING

Q: Why are the lights connected to the driver blinking roughly once a second?

A: The driver may be overloaded. Check to make sure the maximum wattage is not being exceeded. There could also be a possibility of incompatible voltage. Confirm that the driver and tape light voltage match.

Q: How do I determine the compatibility?

A: Check the voltage, wattage, load capacity of both the tape light and driver.

Q: Is it possible to have multiple runs of tape light that are daisy-chained together connect to a driver with 1 lead wire?

A: Yes, but only if the total length of consecutive runs do not exceed the tape light's maximum run and also does not exceed the driver's maximum wattage.