







Casambi Knowledge Ba



Download FREE Casamb iOS/Android App




Specification Librar

Project:	
Reference Type:	
tem Code:	
Date:	
Notes:	

# ALLOYLED°

Name Casambi PWM5 Pro SKU AL-60-04-0008

### **PWM5 Pro - Constant Voltage LED Driver**




#### Description

PWM5 Pro is a 5-channel PWM dimmer designed for controlling constant-voltage LED loads, such as LED strips and modules, It is equipped with Bluetooth connectivity and Casambi-enabled features that allow for easy and convenient control of LED lighting fixtures. The dimmer is installed between a 12-24 VDC power supply and the constant-voltage LED load.

Each channel of the PWM5 Pro is capable of delivering a maximum output current of 4A, and the combined total output current of all channels is 10A max. Additionally, the device is protected against overload and provides flicker-free lighting experience.

### Control

Dimmable by Casambi app which can be downloaded free of charge from Apple App Store and Google Play Store.



#### **Properties**

 Input Voltage:
 12-24V DC

 Max. input current:
 10A

 Max. output current:
 10A (4A/ch)

 Output Voltage :
 Same as input

 Max Output Power:
 120W @12VDC / 240W @24VDC

Wire type: 14-22AWG

Device Control: PWM by Casambi App Case size: 100 x 47 x h 23 mm

Weight: 51g
Protection: IP20
Operating temp: -20 to 50°C
Installation: Remote

Control options: Available profiles

1-5 channels 1-5 channels independent-channel

2 channels CCT Tunable white

 3 channels
 RGB

 4 channels
 RGBW

 4 channels
 RGB+White

 5 channels
 RGBTW / RGBWA

 5 channels
 RGB + TW

CE, FCC, LVD(2014/35/EU)\*\*



NOTES: \*\*Low Voltage Directive (2014/35/EU): The products applicative voltage is under 75VDC of LVD minimum adopted voltage. For more information and user manual please contact: sales@ledbydesign.asia

We reserve the right to change specifications without prior notification.














Project:	
Reference Type:	
Item Code:	
Date:	
Notes:	

## ALLOYLED

Name	Casambi PWM5 Pro
SKU	AL-60-04-0008

### **Multiple Channel Option Diagrams:**



NOTES: \*\*Low Voltage Directive (2014/35/EU): The products applicative voltage is under 75VDC of LVD minimum adopted voltage. For more information and user manual please contact: sales@ledbydesign.asia

We reserve the right to change specifications without prior notification









Casambi Knowledge Ba



Download FREE Casamb iOS/Android App




Specification Librar

Project:	
Reference Type:	
Item Code:	
Date:	
Notes:	

# ALLOYLED°

Name Casambi PWM5 Pro SKU AL-60-04-0008



NOTES: \*\*Low Voltage Directive (2014/35/EU): The products applicative voltage is under 75VDC of LVD minimum adopted voltage.

For more information and user manual please contact: sales@ledbydesign.asia

We reserve the right to change specifications without prior notification