

ALLOYLED®

GRAZE WITH PRECISION

FocaLine 6 A Complete Fixture

Flexible Wall Grazer



Focused Beam Angle

Offers a beam angle of only **10°** to effortlessly skim the surface of walls, accentuating its texture with **precision**.



4000+ Peak Center Beam Candela

Boasts a slim profile and low power consumption, yet delivers an impressive, high performance **4000+ peak center beam candela**.



Available in Wet Location

When ordered through our customization department, FocaLine 6 is rated for wet locations with **factory-sealed connections**.

| Channel Prefix | Location | Tape Model | Voltage | CCT** | Lens | Finish | Length | # of Leads | Lead Length 1 | Lead Length 2 |
|-------------------|---------------------|------------|---------|----------------------------------|---------------------------------|--------------------|---------------|----------------|---------------|---------------|
| AL-SFU-Focaline6- | O <i>Outdoor</i> | FocaLine6 | 24V | 2700K 3000K 3500K 4000K | With Louvers Without Louvers | BL <i>Black</i> | <i>inches</i> | 1LEAD 2LEAD | <i>inches</i> | <i>inches</i> |

Included in Fixture

Anti-glare louvers (Optional)

Recommended for when the light beam is visible, such as in a walkway shining light up a wall or a lower exposed wall at eye level.

Inner clips securely mount FocaLine 6 into the channel.

Create longer lengths by linking FocaLine 6 channels together with the **straight connectors** that slide into the tracks at the bottom of the channel.

Mounting clips are secured to the installation surface with provided screws. The channel securely clicks into the clip.

Sleek, beautiful **channel** securely houses **Focaline 6** for easy installation.

Optional Accessory



Adjustable Bracket

AL-01-76-9986-AL

The **adjustable bracket** is designed to allow precise positioning of the channel at 0°, 30°, 60° or 90° and can be securely mounted to various surfaces.

Order Now!



Email: solutions@AlloyLED.com



Call: 800.910.LEDS (5337)



Fax: 510.338.6173