

PrimaLine® 1.5 Wet Location LED Tape Light



Actual size shown



0.4 in. wide



PrimaLine 1.5 Wet Location Tape Light offers all the same benefits and features as the PrimaLine 1.5 for wet locations outdoors and indoors. At only 1.5 watts per foot, this tape offers the perfect brightness for ambient and close application, task, cabinet, and shelf lighting. A silicone coating protects against water and elements like dust and grease, and foot traffic.

- Perfect for wet or dusty locations and high traffic locations
- Indoor and outdoor use
- Sturdy but flexible
- 6-year warranty

TECHNICAL INFORMATION

Color Temperature	2700K, 3000K, 4200K, 5000K*
Power Consumption per Foot	1.44 Watts/120mA
Input Voltages	12V DC
Diodes per foot	18
Diode Spacing	0.65 inches
Tape Height	0.2 inches
Beam Angle	120°
12V Field Cuttable (UL 2108)	Every 2 inches
Maximum Run Length	34 ft.
Dimmable	Yes
Diode Type	3528 SMD
Diode Brand	Epistar

Mounting	3M™ Self-Adhesive Tape (Acrylic Foam), Mounting Clips (Included)
Operating Temperature	-13° F to 140° F
Ambient Temperature	-40° F to 186° F
Spool Lengths**	16.4 ft.
Environment	Indoor/Outdoor, Dry/Wet, IP68
Certifications	UL Listed, UL 2108, CE, RoHS
Standards	Certified to the CA Energy Commission in accordance with the Title 24 JA8 2016 std.
Warranty	6 Year Limited

* In addition to stocked colors, a wide variety of Color Temperature is also available by special order. Please call or email to order.

** Each spool includes 36 in., 20 AWG tinned lead wires at both ends of the tape light.

PRODUCT INFORMATION

16.4 ft. spool Item Number	Voltage	Color Temperature	CRI	R9 Value	R13 Value	TM30	CQS	Lumens per Foot
AL-01-01-1261	12V DC	2700K	96.9	86.4	97.2	93.6	92.9	93
AL-01-01-1262	12V DC	3000K	94.9	78.3	95.1	91.2	92.5	103
AL-01-01-1263	12V DC	4200K	95	87	96	90.4	93.1	123
AL-01-01-1264	12V DC	5000K	95	97	98	90	92.7	117

ALLOY LED® Specifications

VOLTAGE DROP GUIDANCE CHART


Standard Non-XT 12V Voltage Drop and Wire Length Distance Chart (3% Drop or 11V)

Wire Gauge	Copper Wire Resistance (Ω/kFT)	10W (0.83A)	20W (1.67A)	30W (2.50A)	40W (3.33A)	50W (4.17A)	60W (5A)
22 AWG	16.14	14 ft.	7 ft.	5 ft.	4 ft.	3 ft.	3 ft.
20 AWG	10.15	22 ft.	11 ft.	8 ft.	6 ft.	5 ft.	4 ft.
18 AWG	6.39	34 ft.	17 ft.	12 ft.	9 ft.	7 ft.	6 ft.
16 AWG	4.02	54 ft.	27 ft.	18 ft.	14 ft.	11 ft.	9 ft.
14 AWG	2.53	86 ft.	43 ft.	29 ft.	22 ft.	18 ft.	15 ft.
12 AWG	1.59	137 ft.	69 ft.	46 ft.	35 ft.	28 ft.	23 ft.
10 AWG	0.99	217 ft.	109 ft.	73 ft.	55 ft.	44 ft.	37 ft.

Note: These tables provide general guidelines for determining Wire Gauge based on total load and distance from LED driver to beginning of luminaire.

ACCESSORIES (INCLUDED)


Mounting and Installation Accessories



5 Splice Sleeves



10 Waterproof End Caps




10 Mounting Clips
20 Screws


ACCESSORIES (SOLD SEPARATELY)

Wet Location Junction Boxes


Provide a waterproof seal for wire connections, and are useful for connections between LED fixtures and low voltage power.




AL-98-05-99001



AL-98-05-99002-2














AL-98-05-99002-3



AL-98-05-99002-4

Item Number	Description	Maximum Voltage	Dimensions
AL-98-05-99001	Waterproof Cable Interconnector	450V AC	2.05 x 0.84 x 0.84 in.
AL-98-05-99002-2	Waterproof Junction Box - 2 Port	450V AC	5.5 x 2.25 x 1.46 in.
AL-98-05-99002-3	Waterproof Junction Box - 3 Port	450V AC	5.5 x 3.1 x 1.46 in.
AL-98-05-99002-4	Waterproof Junction Box - 4 Port	450V AC	5.5 x 4.1 x 1.46 in.





Reduced Hotspot Pairings (Hotspot Rating from 0-5)

<p>Surfa 2: Corner-Mount</p>  <p>Hotspot Rating: 2</p> <ul style="list-style-type: none"> <input checked="" type="checkbox"/> Solder <input checked="" type="checkbox"/> Connector <input type="checkbox"/> TapeMate 	<p>Surfa 2X: Corner-Mount</p>  <p>Hotspot Rating: 0</p> <ul style="list-style-type: none"> <input checked="" type="checkbox"/> Solder <input checked="" type="checkbox"/> Connector <input type="checkbox"/> TapeMate 	<p>Surfa 6 Surround: Surface-Mount</p>  <p>Hotspot Rating: 0</p> <ul style="list-style-type: none"> <input checked="" type="checkbox"/> Solder <input checked="" type="checkbox"/> Connector <input type="checkbox"/> TapeMate
<p>Surfa 7: Surface-Mount</p>  <p>Hotspot Rating: 1</p> <ul style="list-style-type: none"> <input checked="" type="checkbox"/> Solder <input checked="" type="checkbox"/> Connector <input type="checkbox"/> TapeMate 	<p>Suspan 1: Suspended</p>  <p>Hotspot Rating: 0</p> <ul style="list-style-type: none"> <input checked="" type="checkbox"/> Solder <input checked="" type="checkbox"/> Connector <input type="checkbox"/> TapeMate 	<p>Ankr 1: In-Wall</p>  <p>Hotspot Rating: 1</p> <ul style="list-style-type: none"> <input checked="" type="checkbox"/> Solder <input checked="" type="checkbox"/> Connector <input type="checkbox"/> TapeMate
<p>Ankr 2: In-Wall</p>  <p>Hotspot Rating: 0</p> <ul style="list-style-type: none"> <input checked="" type="checkbox"/> Solder <input checked="" type="checkbox"/> Connector <input type="checkbox"/> TapeMate 	<p>Ankr 3: In-Wall</p>  <p>Hotspot Rating: 1</p> <ul style="list-style-type: none"> <input checked="" type="checkbox"/> Solder <input checked="" type="checkbox"/> Connector <input type="checkbox"/> TapeMate 	<p>Ankr 4: Mud-In</p>  <p>Hotspot Rating: 1</p> <ul style="list-style-type: none"> <input checked="" type="checkbox"/> Solder <input checked="" type="checkbox"/> Connector <input type="checkbox"/> TapeMate
<p>Duro 1: In-Ground</p>  <p>Hotspot Rating: 0</p> <ul style="list-style-type: none"> <input checked="" type="checkbox"/> Solder <input checked="" type="checkbox"/> Connector <input type="checkbox"/> TapeMate 	<p>Duro 2: In-Ground</p>  <p>Hotspot Rating: 2</p> <ul style="list-style-type: none"> <input checked="" type="checkbox"/> Solder <input checked="" type="checkbox"/> Connector <input type="checkbox"/> TapeMate 	

ALLOY LED® Specifications

COMPATIBLE CHANNELS (Diagrams below not to scale)

Other Compatible Pairings (Hotspot Rating from 0-5)


<p>Surfa 1: Surface-Mount</p>  <p>Hotspot Rating: 3</p> <ul style="list-style-type: none"> <input checked="" type="checkbox"/> Solder <input type="checkbox"/> Connector <input type="checkbox"/> TapeMate 	<p>Surfa 6: Surface-Mount</p>  <p>Hotspot Rating: 5</p> <ul style="list-style-type: none"> <input checked="" type="checkbox"/> Solder <input checked="" type="checkbox"/> Connector <input type="checkbox"/> TapeMate 	<p>Naro 4: Recessed</p>  <p>Hotspot Rating: 5</p> <ul style="list-style-type: none"> <input checked="" type="checkbox"/> Solder <input checked="" type="checkbox"/> Connector <input type="checkbox"/> TapeMate
<p>Polymer: Surface-Mount</p>  <p>Hotspot Rating: 5</p> <ul style="list-style-type: none"> <input checked="" type="checkbox"/> Solder <input checked="" type="checkbox"/> Connector <input type="checkbox"/> TapeMate 		

ALLOY LED[®] Specifications


RECOMMENDED POWER SUPPLIES (SOLD SEPARATELY)



Alloy LED PowerFactor™ Dimmable Power Supplies with Integrated UL Listed Junction Box
Compact, highly efficient, and code-compliant power supply with versatile and smooth dimming capabilities.



Wiring diagram is for reference only. Please refer to dimmer wiring specifications sheet for accurate directions.



Single Tap Models

Item Number	Output Voltage	Wattage	Wet Location	Minimum Load	Dimensions (L x W x H)	Class 2
AL-98-10-12030	12V DC	30W	Yes (NEMA 4X)	10%	6.50 x 3.72 x 1.02 in.	Yes
AL-98-10-12060	12V DC	60W	Yes (NEMA 4X)	10%	7.40 x 3.72 x 1.02 in.	Yes
AL-98-10-12120	12V DC	120W	Yes (NEMA 4X)	10%	8.66 x 3.72 x 1.57 in.	No
AL-98-10-24030	24V DC	30W	Yes (NEMA 4X)	10%	6.50 x 3.72 x 1.02 in.	Yes
AL-98-10-24060	24V DC	60W	Yes (NEMA 4X)	10%	7.40 x 3.72 x 1.02 in.	Yes
AL-98-10-24096	24V DC	96W	Yes (NEMA 4X)	10%	8.66 x 3.72 x 1.57 in.	Yes
AL-98-10-24150	24V DC	150W	Yes (NEMA 4X)	10%	10.24 x 4.13 x 1.77 in.	No
AL-98-10-24200	24V DC	200W	Yes (NEMA 4X)	10%	10.24 x 4.13 x 1.77 in.	No
AL-98-10-24300	24V DC	300W	Yes (NEMA 4X)	10%	10.94 x 4.33 x 1.77 in.	No

Class 2 Compliant Multi-Tap Models

Item Number	Output Voltage	Wattage	Wet Location	Minimum Load	Dimensions (L x W x H)	Class 2
AL-98-10-12300-MT	12V DC	300W	Yes (NEMA 4X)	10%	11.85 x 4.33 x 1.77 in.	Yes
AL-98-10-24192-MT	24V DC	192W	Yes (NEMA 4X)	10%	10.94 x 4.33 x 1.77 in.	Yes
AL-98-10-24288-MT	24V DC	288W	Yes (NEMA 4X)	10%	11.85 x 4.33 x 1.77 in.	Yes

Note: PowerFactor assumes 80% load.
Inspectors prefer power supply to be used with junction box.
For dimmer compatibility, refer to drivers specification sheet.

ALLOY LED® Specifications

RECOMMENDED POWER SUPPLIES (SOLD SEPARATELY)


Alloy LED Primavolt® No Minimum Load Dimmable Power Supplies with ETL Listed Junction Box
Code-compliant power supply with versatile and smooth dimming capabilities. Compatible with Incandescent, On/Off, ELV and MLV dimmers.




Dry Location Model
White model for 60W and lower



Wet Location Model
Black model for 80W and higher



Wiring diagram is for reference only. Please refer to dimmer wiring specifications sheet for accurate directions.



Item Number	Output Voltage	Wattage	Minimum Load	Dimensions (Junction Box) (L x W x H)	Class 2
AL-98-03-12024-NM	12V DC	24W	0%	13.78 x 3.03 x 1.46 in.	Yes
AL-98-03-12048-NM	12V DC	48W	0%	13.78 x 3.03 x 1.46 in.	Yes
AL-98-03-12060-NM	12V DC	60W	0%	13.78 x 3.03 x 1.46 in.	Yes
AL-98-03-12080-NM	12V DC	80W	0%	14.96 x 3.03 x 2.24 in.	No
AL-98-03-12120-NM	12V DC	120W	0%	14.96 x 3.03 x 2.24 in.	No
AL-98-03-24024-NM	24V DC	24W	0%	13.78 x 3.03 x 1.46 in.	Yes
AL-98-03-24048-NM	24V DC	48W	0%	13.78 x 3.03 x 1.46 in.	Yes
AL-98-03-24060-NM	24V DC	60W	0%	13.78 x 3.03 x 1.46 in.	Yes
AL-98-03-24080-NM	24V DC	80W	0%	14.96 x 3.03 x 2.24 in.	Yes
AL-98-03-24096-NM	24V DC	96W	0%	14.96 x 3.03 x 2.24 in.	Yes
AL-98-03-24150-NM	24V DC	150W	0%	15.98 x 3.43 x 2.36 in.	No
AL-98-03-24200-NM	24V DC	200W	0%	15.98 x 3.43 x 2.36 in.	No


Note: Alloy LED strongly recommends using Listed Class 2 power supplies for all installations. Always install in accordance with local and national electrical code regulations. Inspectors prefer power supply to be used with junction box. For dimmer compatibility, refer to drivers specification sheet.

ALLOY LED® Specifications


RECOMMENDED POWER SUPPLIES (SOLD SEPARATELY)

ELV Dimmable Power Supplies for Remote Enclosures

The drivers are derated, but when installed in a small enclosure with no heatsink or air circulation, we recommend a maximum load of 40W.



Wiring diagram is for reference only. Please refer to dimmer wiring specifications sheet for accurate directions.



Item Number	Output	Wattage	Dimensions (L x W x H)	Class 2
AL-98-08-12060	12V DC	60W	2.66 x 1.30 x 0.83 in.	Yes
AL-98-08-24060	24V DC	60W	2.66 x 1.30 x 0.83 in.	Yes

Note: Inspectors prefer power supply to be used with junction box.
For dimmer compatibility, refer to drivers specification sheet.

ALLOY LED® Specifications

DIMMING ACCESSORIES (SOLD SEPARATELY)

Lutron® Dimming Accessories

By participating in Lutron's OEM Advantage program, Alloy LED is able to offer a range of the highest quality low voltage power supplies and selected controls on the market.



Hi-lume Premier
0.1% EcoSystem /
3-wire LED Driver
(96W 24VDC)



Hi-lume 1% LED Driver 40W
- EcoSystem / 3-wire control
- 2-wire 120V forward
phase control



Lutron Vive PowPak RF Module
- RF module for EcoSystem LED
driver control
- Use with the Lutron EcoSystem
drivers shown to "Vive-enable"
Alloy LED products

Lutron® Hi-lume LED Drivers

Item Number	Output	Wattage	Minimum Load	Class 2
AL-98-07-12040	12V DC	40W	N/A	Yes
AL-98-07-12040-3WIRE	12V DC	40W	N/A	Yes
AL-98-07-24040	24V DC	40W	N/A	Yes
AL-98-07-24040-3WIRE	24V DC	40W	N/A	Yes
AL-98-07-24096-3WIRE	24V DC	96W	N/A	Yes

Lutron® Controls

Item Number	Description	Voltage
AL-98-07-9901	EcoSystem Control Module	N/A
AL-98-07-9901-8	EcoSystem Control Module - 8-pack	N/A
AL-98-07-9950	CL Dimmer	120V AC
AL-98-07-9950-FPLATE	CL Dimmer faceplate	N/A


DIMMING ACCESSORIES (SOLD SEPARATELY)

Dimmers and Switches

SlimDim Wireless Dimmer Switch

Using long-range RF technology, these LED dimmers connect wirelessly to a receiver, offering freedom to mount anywhere. Can also be used as a fob for mobile, hand-held control.


AL-70-01-0001	SlimDim Wireless Dimmer
AL-70-01-0002	Single Color Receiver (96W max.) (sold separately)
AL-98-07-9950 -FPLATE	SlimDim Wall Plate (sold separately)



Remote Control Dimmer Switch

Provides full dimming and on/off control, and includes a touch wheel that allows for direct visual selection of brightness. It can also operate up to four independent zones.


AL-60-03-0001	Remote Control Dimmer Switch
AL-70-01-0002	Single Channel Receiver (sold separately)
AL-60-03-0004-V2	Wireless Receiver (RGB & RGBW) (sold separately)




Single Channel Wireless Receiver

Pair with the Remote Control Dimmer Switch or the SlimDim Wireless Dimmer to dim PrimaLine tape lights. Use one remote to make independent lighting zones with multiple receivers with certain controllers.

AL-70-01-0002	Single Channel Wireless Receiver
---------------	----------------------------------



WIRING DIAGRAM




ALLOY LED® Specifications


RECOMMENDED POWER SUPPLIES (SOLD SEPARATELY)

Alloy LED TRIAC/MLV/ELV Dimmable Drivers for Remote Locations

Offers stable power in even in the most remote settings. Compatibility with TRIAC, ELV, or MLV dimmers.



Wiring diagram is for reference only. Please refer to dimmer wiring specifications sheet for accurate directions.





Item Number	Output Voltage	Wattage	Dimensions (L x W x H)	Class 2
AL-98-09-12060	12V DC	60W	3.31 x 1.57 x 0.98	Yes
AL-98-09-24096	24V DC	96W	3.31 x 1.57 x 0.98	Yes


Note: Alloy LED strongly recommends using Listed Class 2 power supplies for all installations. Always install in accordance with local and national electrical code regulations. Inspectors prefer power supply to be used with junction box. For dimmer compatibility, refer to drivers specification sheet.

Note: specifications are representative of the diode type and not a particular tape light article.


2700K



TM30: 93.6



CRI: 96.9 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
97.5	97.1	95.5	98.1	96.5	96.8	98.5	95.0	86.4	92.5	99.3	84.3	97.2	96.7	95.2


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
94.8	96.7	96.0	92.1	94.0	95.1	91.6	94.7	93.2	90.8	91.5	93.5	95.4	93.5	93.6	90.8

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
92.1	95.5	94.1	93.7	94.7	95.0	95.6	94.2	91.5	88.5	90.1	92.0	94.2	94.0	94.5

CQS: 92.9



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
2801 K	96.9	86.4	93.6	97.8	92.9	0.458	0.419	0.257	0.354	0.0034







Note: specifications are representative of the diode type and not a particular tape light article.

2700K

Rf 93.6
Fidelity index Rf


Rg 97.8
Gammut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	95	-2%	0%
2	97	-1%	-1%
3	96	-2%	0%
4	92	-5%	-2%
5	94	-4%	1%
6	95	-2%	2%
7	92	-4%	3%
8	95	-1%	3%
9	93	-1%	4%
10	91	0%	5%
11	92	2%	5%
12	94	3%	0%
13	95	0%	-3%
14	93	2%	-4%
15	94	-2%	0%
16	91	0%	-6%



Note: specifications are representative of the diode type and not a particular tape light article.

2700K



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
37lx	9lx	4lx	2lx	1lx	1lx	1lx	1lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx
3.4fcd	0.9fcd	0.4fcd	0.2fcd	0.1fcd	0.1fcd	0.1fcd	0.1fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd

Intensities in 0° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
37.0	37.0	36.6	36.0	35.2	34.1	32.6	30.9	28.9	26.6	24.2	21.6	18.7	15.6	12.3	8.9	5.7	3.0	1.2	0.4
100%	100%	99%	97%	95%	92%	88%	83%	78%	72%	65%	58%	50%	42%	33%	24%	15%	8%	3%	1%

Intensities in 90° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
37.0	37.0	36.6	36.0	35.2	34.1	32.6	30.9	28.9	26.6	24.2	21.6	18.7	15.6	12.3	8.9	5.7	3.0	1.2	0.4
100%	100%	99%	97%	95%	92%	88%	83%	78%	72%	65%	58%	50%	42%	33%	24%	15%	8%	3%	1%

Intensities in 180° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
37.0	36.8	36.2	35.4	34.3	32.9	31.2	29.5	27.7	25.6	23.4	21.0	18.6	16.1	13.4	10.6	7.7	5.0	2.5	0.7
100%	99%	98%	96%	93%	89%	84%	80%	75%	69%	63%	57%	50%	43%	36%	29%	21%	13%	7%	2%



Intensities in 270° c-plane

0°	5°	10°	15°	20°	25°	30°	35°	40°	45°	50°	55°	60°	65°	70°	75°	80°	85°	90°	95°
37.0	36.8	36.2	35.4	34.3	32.9	31.2	29.5	27.7	25.6	23.4	21.0	18.6	16.1	13.4	10.6	7.7	5.0	2.5	0.7
100%	99%	98%	96%	93%	89%	84%	80%	75%	69%	63%	57%	50%	43%	36%	29%	21%	13%	7%	2%


Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
120.4°	171.1°	185.2°	72.3%	48.1%

Note: specifications are representative of the diode type and not a particular tape light article.


3000K



TM30: 91.2



CRI: 94.9 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
94.9	96.4	96.9	94.3	93.6	95.3	96.6	91.0	78.3	90.7	94.5	79.3	95.1	97.6	92.4


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
92.0	94.7	95.0	91.6	91.2	94.2	88.2	92.4	89.4	85.2	88.7	92.3	94.3	91.5	90.1	88.5

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
90.5	95.2	92.7	90.3	91.1	91.3	93.3	94.7	93.3	90.7	92.7	93.9	94.9	92.5	92.8

CQS: 92.5



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color division from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
3051 K	94.9	78.3	91.2	96.8	92.5	0.439	0.414	0.248	0.350	0.0037







Note: specifications are representative of the diode type and not a particular tape light article.

3000K

Rf 91.2
Fidelity index Rf


Rg 96.8
Gammut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	92	-3%	1%
2	95	-2%	0%
3	95	-2%	0%
4	92	-4%	-1%
5	91	-7%	0%
6	94	-3%	1%
7	88	-6%	4%
8	92	-3%	4%
9	89	-2%	6%
10	85	0%	8%
11	89	2%	7%
12	92	4%	0%
13	94	0%	-3%
14	91	2%	-5%
15	90	-2%	-3%
16	88	-1%	-7%



Note: specifications are representative of the diode type and not a particular tape light article.

3000K



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
25lx	6lx	3lx	2lx	1lx	1lx	1lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx
2.3fcd	0.6fcd	0.3fcd	0.1fcd	0.1fcd	0.1fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd

Intensities in 0° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
24.9	24.6	23.8	22.5	20.5	18.2	15.5	12.9	9.9	6.3	3.7	2.4	2.5	2.9	3.7	4.1	0.6	0.5	0.5	0.5
100%	99%	96%	90%	83%	73%	62%	52%	40%	26%	15%	10%	10%	12%	15%	17%	2%	2%	2%	2%

Intensities in 90° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
24.9	24.6	23.8	22.5	20.5	18.2	15.5	12.9	9.9	6.3	3.7	2.4	2.5	2.9	3.7	4.1	0.6	0.5	0.5	0.5
100%	99%	96%	90%	83%	73%	62%	52%	40%	26%	15%	10%	10%	12%	15%	17%	2%	2%	2%	2%

Intensities in 180° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
24.9	24.7	24.2	22.9	21.2	19.0	16.2	13.0	9.9	6.5	3.1	2.4	2.9	4.1	3.5	2.2	0.8	0.5	0.5	0.4
100%	100%	97%	92%	85%	76%	65%	52%	40%	26%	12%	10%	12%	16%	14%	9%	3%	2%	2%	2%



Intensities in 270° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
24.9	24.7	24.2	22.9	21.2	19.0	16.2	13.0	9.9	6.5	3.1	2.4	2.9	4.1	3.5	2.2	0.8	0.5	0.5	0.4
100%	100%	97%	92%	85%	76%	65%	52%	40%	26%	12%	10%	12%	16%	14%	9%	3%	2%	2%	2%


Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
129°	269.4°	289.8°	59.3%	38.8%

Note: specifications are representative of the diode type and not a particular tape light article.


4200K



TM30: 90.4



CRI: 94.2 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
94.1	95.2	94.5	93.8	92.4	91.5	98.2	93.6	81.9	87.4	92.9	69.3	94.3	96.7	93.0


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
91.8	94.7	93.4	91.9	91.2	95.7	93.1	91.8	87.8	83.0	82.6	90.5	93.2	93.7	88.1	87.1

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
93.8	99.0	87.7	86.0	90.1	91.9	94.5	96.6	97.8	95.9	95.4	96.1	96.7	95.1	95.4

CQS: 93.1



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
4370 K	94.2	81.9	90.4	98.5	93.1	0.367	0.374	0.217	0.332	0.0028







Note: specifications are representative of the diode type and not a particular tape light article.

4200K

Rf 90.4
Fidelity index Rf


Rg 98.5
Gammut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	92	-3%	0%
2	95	-2%	0%
3	93	-1%	2%
4	92	-3%	1%
5	91	-4%	0%
6	96	-1%	0%
7	93	-4%	1%
8	92	-3%	3%
9	88	-4%	8%
10	83	-2%	10%
11	83	3%	10%
12	91	3%	4%
13	93	4%	-1%
14	94	1%	-2%
15	88	2%	-6%
16	87	1%	-7%



Note: specifications are representative of the diode type and not a particular tape light article.

4200K



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
29lx	7lx	3lx	2lx	1lx	1lx	1lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx
2.7fcd	0.7fcd	0.3fcd	0.2fcd	0.1fcd	0.1fcd	0.1fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd

Intensities in 0° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
29.2	28.8	27.9	26.6	24.6	22.1	18.9	15.3	11.3	7.6	3.9	2.6	3.1	4.0	5.0	1.6	0.6	0.6	0.6	0.6
100%	99%	96%	91%	84%	76%	65%	52%	39%	26%	13%	9%	11%	14%	17%	5%	2%	2%	2%	2%

Intensities in 90° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
29.2	28.8	27.9	26.6	24.6	22.1	18.9	15.3	11.3	7.6	3.9	2.6	3.1	4.0	5.0	1.6	0.6	0.6	0.6	0.6
100%	99%	96%	91%	84%	76%	65%	52%	39%	26%	13%	9%	11%	14%	17%	5%	2%	2%	2%	2%

Intensities in 180° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
29.2	29.0	28.3	27.1	25.0	22.3	19.0	15.3	11.1	6.9	3.2	2.6	3.5	4.6	5.4	4.7	2.9	2.2	1.0	0.6
100%	99%	97%	93%	86%	76%	65%	52%	38%	24%	11%	9%	12%	16%	19%	16%	10%	8%	3%	2%



Intensities in 270° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
29.2	29.0	28.3	27.1	25.0	22.3	19.0	15.3	11.1	6.9	3.2	2.6	3.5	4.6	5.4	4.7	2.9	2.2	1.0	0.6
100%	99%	97%	93%	86%	76%	65%	52%	38%	24%	11%	9%	12%	16%	19%	16%	10%	8%	3%	2%


Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
129°	275.2°	302.4°	59.4%	38.8%

Note: specifications are representative of the diode type and not a particular tape light article.


5000K



TM30: 90.0



CRI: 93.6 (R1-R8)



CRI R values, only R1-R8 are used to calculate final CRI value

R1	R2	R3	R4	R5	R6	R7	R8	R9	R10	R11	R12	R13	R14	R15
93.4	94.4	93.6	93.6	92.0	90.4	98.0	93.4	80.5	85.6	92.5	68.3	93.6	96.3	92.6


TM30 C values, 16 binned values out of total of 99 C values

C1	C2	C3	C4	C5	C6	C7	C8	C9	C10	C11	C12	C13	C14	C15	C16
91.7	95.2	92.9	91.6	91.0	95.5	93.1	89.8	87.4	82.2	81.1	89.3	93.1	93.4	87.7	86.1

CQS Q values

Q1	Q2	Q3	Q4	Q5	Q6	Q7	Q8	Q9	Q10	Q11	Q12	Q13	Q14	Q15
94.5	99.3	86.5	85.2	89.9	91.7	94.0	96.4	97.4	94.9	94.5	95.5	96.2	94.6	95.2

CQS: 92.7



Color parameters

Color temperature	Color rendering index	Red component	Color fidelity	Color gamut	Color quality scale	Color coordinate cie 1931	Color coordinate cie 1931	Color coordinate	Color coordinate	Color deviation from black body
CCT	CRI	CRI R9	TM30 Rf	TM30 Rg	CQS	x	y	u	v	Δuv
4684 K	93.6	80.5	90.0	98.5	92.7	0.356	0.365	0.213	0.329	0.0028







Note: specifications are representative of the diode type and not a particular tape light article.

5000K

Rf 90.0
Fidelity index Rf


Rg 98.5
Gammut index Rg

Hue Bin	R _f	Graphic shifts (%)	
		Chroma	Hue
1	92	-3%	0%
2	95	-2%	1%
3	93	-2%	1%
4	92	-3%	1%
5	91	-4%	1%
6	95	-1%	0%
7	93	-4%	0%
8	90	-4%	3%
9	87	-4%	9%
10	82	-2%	10%
11	81	3%	11%
12	89	4%	4%
13	93	5%	-1%
14	93	2%	-2%
15	88	3%	-6%
16	86	1%	-8%



Note: specifications are representative of the diode type and not a particular tape light article.

5000K



Beam intensities from 1-20m

1m	2m	3m	4m	5m	6m	7m	8m	9m	10m	11m	12m	13m	14m	15m	16m	17m	18m	19m	20m
3.3ft	6.6ft	9.8ft	13.1ft	16.4ft	19.7ft	23ft	26.2ft	29.5ft	32.8ft	36.1ft	39.4ft	42.7ft	45.9ft	49.2ft	52.5ft	55.8ft	59.1ft	62.3ft	65.6ft
28lx	7lx	3lx	2lx	1lx	1lx	1lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx	0lx
2.6fcd	0.7fcd	0.3fcd	0.2fcd	0.1fcd	0.1fcd	0.1fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd	0fcd

Intensities in 0° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
28.3	27.9	27.0	25.6	23.7	21.0	17.8	14.1	10.1	6.2	3.0	2.6	3.8	5.0	5.4	4.3	2.4	1.2	0.6	0.6
100%	99%	95%	91%	84%	74%	63%	50%	36%	22%	10%	9%	13%	18%	19%	15%	8%	4%	2%	2%

Intensities in 90° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
28.3	27.9	27.0	25.6	23.7	21.0	17.8	14.1	10.1	6.2	3.0	2.6	3.8	5.0	5.4	4.3	2.4	1.2	0.6	0.6
100%	99%	95%	91%	84%	74%	63%	50%	36%	22%	10%	9%	13%	18%	19%	15%	8%	4%	2%	2%

Intensities in 180° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
28.3	28.3	27.5	26.0	23.9	21.1	17.8	14.1	10.2	6.0	2.8	2.6	3.5	5.1	5.8	2.2	0.6	0.6	0.7	0.7
100%	100%	97%	92%	84%	75%	63%	50%	36%	21%	10%	9%	12%	18%	21%	8%	2%	2%	2%	2%

Intensities in 270° c-plane

0°	9°	18°	27°	36°	45°	54°	63°	72°	81°	90°	99°	108°	117°	126°	135°	144°	153°	162°	171°
28.3	28.3	27.5	26.0	23.9	21.1	17.8	14.1	10.2	6.0	2.8	2.6	3.5	5.1	5.8	2.2	0.6	0.6	0.7	0.7
100%	100%	97%	92%	84%	75%	63%	50%	36%	21%	10%	9%	12%	18%	21%	8%	2%	2%	2%	2%

Beam angle 50%	Field angle 10%	Cutoff angle 2,5%	Intensity ratio in 120° cone	Intensity ratio in 90° cone
125.8°	273.2°	335.5°	59.5%	39.1%